

AIJGO-22/ALU Footwear & Wrist Strap Tester with Dual Foot Electrode

The AIJGO-22/ALU is an easy usable Footwear & Wrist strap tester to entrance of EPA area. It is versatile tester because you can choose the right measuring methods according to entrance regulation: Only footwear testing or footwear and wrist strap combined testing. You have to make only one test at the same time for the left and right foot because of the dual foot electrode. It can be connected to any kind of entrance gate (tripod turnstile, swing gate, wing barrier,...) with a relay output. It can be installed on the wall or with stand to the floor.

- ⇒ Footwear and Wrist Strap Tester for ESD area entrance
- ⇒ Both foot and wrist strap testing at the same time
- ⇒ Dual foot electrode to test the right and left foot separately
- ⇒ Test selector: Only footwear testing or Footwear and wrist strap combined testing
- ⇒ Resistance limits set by Software:

Footwear: 100 K Ω - 35 M Ω - Wrist Strap: 750 K Ω - 35 M Ω

- ⇒ Compliance with IEC 61340-5-1 and ANSI/ESD S20.20
- ⇒ Light (LED) and sound signal for the pass and faulty test, results separately:

Wrist Strap - Left foot - Right foot

- ⇒ Test voltage: 40 V
- ⇒ Steel pushbutton for testing
- ⇒ Wrist Strap connection: 4 mm banan plug or 10 mm snap-fastener
- ⇒ Relay Output to open Entrance gate: 0,5A/60V
- ⇒ Power supply: 12V DC
- ⇒ Size: 215 x 195 x 65 mm



AIJGO-22/ALU



AIJGO-22/ALU + AIJGO-22/STA

ORDER CODE

AIJGO-22/ALU Footwear & Wrist Strap Tester with Dual Foot Electrode

AIJGO-22/STA Stand for AIJGO-22/ALU