



## Portable Indoor Air Quality CO<sub>2</sub> Meter

Measures Carbon Dioxide (CO<sub>2</sub>), Temperature, Humidity, Dew Point, and Wet Bulb And calculates statistical 8 hour and 15 minute time weighted averages

## **Features:**

- Checks for Carbon Dioxide (CO2) concentrations
- Calculates statistical weighted averages of TWA (8 hour time weighted average) and STEL (15 minute short term exposure limit)
- Maintenance free NDIR (non-dispersive infrared) CO<sub>2</sub> sensor
- User programmable audible alarm
- Backlit triple LCD display
- RS-232 interface, Data acquisition software and cable included to analyze data on a PC
- Optional 33% and 75% RH calibration bottles (RH300-CAL)
- Complete with software and cable, 4 AA batteries, and carrying case





Measure CO<sub>2</sub> level in office buildings to check the air quality of conference rooms insuring proper ventilation.

## **Ordering:**

CO250	Portable Indoor Air Quality CO <sub>2</sub> Meter
RH300-CAL .	33% and 75% RH Calibration Kit

Specifications	Range	Resolution
Carbon Dioxide (CO <sub>2</sub> )	0 to 5,000ppm	1ppm
Temperature	-10 to 60°C	0.1°C
Humidity	0.0 to 99.9%	0.1%
Wet Bulb and Dew Point	Calculated	
CE	Yes	
Dimensions/Weight	200x70x57mm/ 190g	

