

DLV7500/8500 series

■ For Machine Screws (2.6 - 6.0 mm)

Features

Low vibration, low noise, and easy gripping in a compact design

- The easily visible torque reach light goes on when the set torque is reached
- The combination of an advanced clutch design and the auto-stop circuit assures torque accuracy
- The long life motor with a yoke made of advanced materials further assures a long service life
- Compliant with CE standard
- Antistatic option is available



DLC4511-GGB



DLR1510-JE

Specifications

Model	Standard	Standard		High Torque	Standard		High Torque
	ESD	DLV7530-MKE	DLV7540-MKE	DLV7550-MKE	DLV8530-MKE	DLV8540-MKE	DLV8550-MKE
Starting Method		Lever Start			Push to Start		
Input Voltage		59 V DC					
Torque Adjustment		Stepless					
Torque (Nm)		0.5 - 1.7	1.2 - 2.7	2.0 - 4.5	0.5 - 1.7	1.2 - 2.7	2.0 - 4.5
Free Speed (min ⁻¹)		1,100	700	500	1,100	700	500
Screw Size (mm)	Machine Screw	2.6 - 4.0	3.5 - 5.0	4.5 - 6.0	2.6 - 4.0	3.5 - 5.0	4.5 - 6.0
	Tapping Screw	2.3 - 3.5	3.0 - 4.0	4.0 - 5.0	2.3 - 3.5	3.0 - 4.0	4.0 - 5.0
Bit Type (mm)							
Mass (g)		650		750	650		750


Measurement point		Conventional product	DLV7500/8500-BKE
		Handle	Static Electricity (V)
Surface Resistance (Ω)	more than 10 ¹³		10 ⁴
Lever Switch	Static Electricity (V)	350	2
	Surface Resistance (Ω)	more than 10 ¹³	10 ⁴
Forward / Reverse Switch	Static Electricity (V)	25	2
	Surface Resistance (Ω)	more than 10 ¹³	10 ¹⁰

Part	Material
Handle Lever Switch	Synthetic resin with carbon fiber
Power Cable	Anti-static material


* Measurement conditions (Temperature:22 °C Humidity:66 %)
 (1) Static electricity • Earth the measurement equipment and measuring person.
 • Grip the screwdriver five times using Ansel Edmont electronic control glove.
 • Turn on the switch of the screwdriver. • Measure each part of the screwdriver using electronic measurement equipment manufactured by Shishido electrostatic Ltd.
 (2) Surface resistance • Measure using Simco Japan surface resistivity measurement equipment.

External Dimensions

DLV7500 series




DLV8500 series



Standard Accessories

Bit	No.	DLV7530 / 7540 / 8530 / 8540	DLV7550 / 8550
Bit	No.1 × 7 × 75	1	—
	No.2 × 7 × 75	1	1
	No.3 × 7 × 50	—	1
Spare Carbon Brush			2
Power Cord			1
Suspension Bail			1



Unit: mm