



**DS017** Length: 13"(330mm) Wt: 3.5oz (99g)

**"The Original" Deluxe SOLDAPULLT®**

- Designed for heavy duty, high volume applications
- Easy one-hand loading and operation
- Integral cleaning shaft self-cleans no-stick PTFE tip



**AS196** Length: 13"(330mm) Wt: 3.5oz (99g)

**SILVERSTAT® SOLDAPULLT®**

- The "Rolls Royce" of static safe desoldering hand tools
- Identical in size and performance to the DS017
- Engineered with conductive plating
- Especially designed for desoldering of static safe components



**DS017LS** Length: 13"(330mm) Wt: 3.5oz (99g)

**Static Safe Deluxe SOLDAPULLT®**

- Same as DS017 but molded from conductive plastic



**PT109** Length: 12"(304mm) Wt: 2.5oz (71g)

**SOLDAPULLT® III**

- Smooth acting, light weight spring loaded tool
- Similar to the DS017 but with petite barrel for smaller hands
- Locking retractable shaft guide for portability and compact storage
- Integral cleaning shaft self-cleans no-stick PTFE tip



**PT409** Length: 12"(304mm) Wt: 2.5oz (71g)

**Static Safe SOLDAPULLT® III**

- Same as PT109 but molded from conductive plastic



**PT209** Length: 12"(304mm) Wt: 2.5oz (71g)

**Micro Tip SOLDAPULLT® III**

- Micro tip version of PT109 for heavily populated circuit boards and precision work
- Light weight petite barrel for smaller hands
- Locking retractable shaft guide for portability and compact storage
- Integral cleaning shaft self-cleans no-stick micro PTFE tip



**US140** Length: 8.5"(216mm) Wt: 1.5oz (43g)

**Universal SOLDAPULLT®**

- Compact single-handed loading system
- Adjustable loading stroke to fit individual needs
- Loading and trigger release done with thumb

\*See page 37 for a complete list of Replacement Tips and O-Rings



**SS011** Length: 8"(203mm) Wt: 1.7oz (49g)

**Static Safe SOLDAPULLT® Successor**

- Static protection for sensitive devices
- Precision engineered metal barrel & static safe PTFE tip
- Simple single handed loading system



**SS102** Length: 8"(203mm) Wt: 1.9oz (54g)

**Micro Tip Static Safe SOLDAPULLT® Successor**

- Micro tip version of SS011 for heavily populated boards and precision work
- Palm grip or finger touch trigger for easier handling
- Precision engineered metal barrel & static safe PTFE tip
- Simple single handed loading system



**SS343** Length: 8.5"(216mm) Wt: 1.4oz (40g)

**Static Safe Pico Tip Challenger SOLDAPULLT®**

- New pointed pico tip for precision desoldering and high vacuum velocity for optimum performance
- Precision engineered metal barrel & static safe PTFE tip
- Simple single-handed loading system
- Static protection for sensitive devices



**SS750LS** Length: 8.5"(216mm) Wt: 1.2oz (34g)

**Economical Static Safe Challenger SOLDAPULLT®**

- Compact static safe barrel
- Quick change tiplet for no hassle maintenance
- Simple single-handed loading system



**SS350** Length: 9"(229mm) Wt: 1.4oz (40g)

**Static Safe Challenger SOLDAPULLT®**

- Outstanding quality for the professional or hobbyist
- Precision engineered metal barrel & static safe PTFE tip
- Simple single-handed loading system
- Adjustable loading stroke to reduce hand strain



**US340** Length: 8.5"(216mm) Wt: 1.5oz (43g)

**Static Safe Universal SOLDAPULLT®**

- Same as US140 but molded from conductive material
- Compact single-handed loading system
- Adjustable loading stroke to fit individual needs
- Loading and trigger release done with thumb

